

LDM HSD UNDERLAY

for LVT NON-SLIP

LDM LVT underlay is high quality mineral based compound laminated with non-slip treatment, its high density provides to the underlay a high resistance to compressive loads and mechanical damages.

LDM LVT underlay is highly suitable for the installation for click PVC/LVT floors.
This product reduces extremely drum and impact sound.

COMPOSITION:

High density mineral, plus SBR or natural latex laminated with PET or Metallized PET film and PP nonwoven treated with non-slip treatment.

Thickness	1,5 ± 0,15 mm
Density	800 ± 80 kg/m ³
Weight	1200 g/m ²
Roll dimension	1x15 m
Packaging	HDPE foil bag
Impact sound reduction	20dB
Drum sound reduction	25%
Castorwheel chair test	Passed
Heat resistance	0,26 togs
Moisture resistance	Sd > 75m



*Informations sur le niveau d'émission de substances volatiles dans l'air intérieur présentées au risque de fausseté par l'industriel, sur une échelle de classe allant de A+ (pas de substances volatiles) à C (très élevées).



Latex del Mediterráneo, S.L.
Polígono Industrial Faima
Calle Calpe, N°56 Nave 24
03330 Crevillente, Alicante (Spain)

LDM
LÁTEX DEL MEDITERRÁNEO, S.L.

Tel.: +34 965 406 628
Fax: +34 965 400 139
www.latexldm.com
ldm@forshoessl.com